KD3-S282AGA / KD3-S282CGA


0.28-inch (7.00 mm) 3-Digit Seven-Segment Display

Yellow Green Surface-Mount Three-Digit LED Numeric Display

LuckyLight
Innovative Optoelectronic Solutions

Technical Data Sheet

Features



- High reliability
- Low current operation
- Low profile and light weight (for space-saving designs)
- Packaged in tape and reel for automated SMT assembly
- Compatible with IR-reflow soldering
- Excellent character appearance
- RoHS compliant

Descriptions

KD3-S282AGA (Common Anode) and KD3-S282CGA (Common Cathode) are 0.28-inch (7.00 mm) character height surface-mount (SMD) yellow green 3-digit seven-segment displays. These devices provide excellent readability at distances up to 7 meters and offer stable performance under high ambient light conditions. The standard version features a gray surface with white segments; a black surface version is also available as an option.

Applications


- **Consumer Electronics:** Home appliances, Game console systems
- **Commercial Terminals:** Point-of-sale terminals
- **General Use:** Digital readout displays
- **Industrial Equipment:** Instrumentation panels, Test and measurement equipment**,** Control systems

Device Selection Guide

Part No.	Emitting Color	Circuit Type
KD3-S282AGA	Yellow Green	Common Anode
KD3-S282CGA	Yellow Green	Common Cathode

Copyright © 2018 Luckylight All Rights Reserved

Package Dimension




Notes:

1. *All dimensions are in millimeters (inches).*
2. *Tolerance is ± 0.25 mm (.010") unless otherwise noted.*
3. *The gap between the reflector and PCB shall not exceed 0.25mm.*


Copyright © 2018 Luckylight All Rights Reserved

Internal Circuit Diagram:

KD3-S282AGA (Common Anode)




KD3-S282CGA (Common Cathode)



Copyright © 2018 Luckylight All Rights Reserved


LuckyLight
Innovative Optoelectronic Solutions

Pin Connection



Pin No.	Function
1	Segment E
2	Segment D
3	DP
4	Segment C
5	Segment G
6	No connect
7	Segment B
8	Digit3 Common
9	Digit2 Common
10	Segment F
11	Segment A
12	Digit1 Common

Recommended Soldering Pattern



Copyright © 2018 Luckylight All Rights Reserved

LuckyLight
Innovative Optoelectronic Solutions

Absolute Maximum Ratings at T_a=25℃

Parameters	Symbol	Max	Unit
Power Dissipation (Per Chip)	P_d	60	mW
Peak Forward Current (Per Segment) (1/10 Duty Cycle, 0.1ms pulse width)	I_{FP}	100	mA
Forward Current (Per Segment)	I_F	25	mA
Reverse Voltage (Per Chip)	V_R	5	V
Operating Temperature Range	T_{opr}	-40℃ to +80℃	
Storage Temperature Range	T_{stg}	-40℃ to +85℃	
Soldering Temperature	T_{sld}	260℃ for 5 Seconds	

Electrical Optical Characteristics at T_a=25℃

Parameters	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Average Luminous Intensity	Iv	3.0	6.0	---	mcd	IF=5mA (Note a)
		6.0	12.0	---	mcd	IF=10mA (Note a)
Luminous Intensity Matching Ratio	I_{v-m}	---	---	2:1		IF=10mA
Peak Emission Wavelength	λp	---	575	---	nm	IF=10mA
Dominant Wavelength	λd	---	572	---	nm	IF=10mA (Note b)
Spectral Line Half-Width	△λ	---	20	---	nm	IF=10mA
Forward Voltage (Per Segment)	V_F	---	1.8	2.4	V	IF=10mA (Note c)
Reverse Current (Per Segment)	I_R	---	---	50	μA	VR=5V

Notes:

a. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve. Tolerance of Luminous Intensity: ± 10 %


b. The dominant wavelength (λd) is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.

c. Tolerance of Forward Voltage: ± 0.1V


Copyright © 2018 Luckylight All Rights Reserved

Typical Electrical/Optical Characteristics Curves (T_a=25 ℃)


Relative Luminous Intensity & Wavelength




Forward Current & Forward Voltage



Relative Luminous Intensity & Forward Current




Forward Current Derating Curve




Copyright © 2018 Luckylight All Rights Reserved

Reel Dimensions *(units: mm)*




Tape Specifications *(units: mm):*




Note: Tolerances unless mentioned ±0.25mm.

Copyright © 2018 Luckylight All Rights Reserved

Packing & Label Specifications



900 pcs/Reel




1 Reel/Bag 1 Bag/Small Box 7 Small Boxes/Box

Copyright © 2018 Luckylight All Rights Reserved

Precautions for Use

1. Pb-Free Reflow Soldering Profile.



(Acc.to-STD-020C)

Pre-heat		Other	
Temperature min	150 ℃	Liquidus Temperature	217℃
Temperature max	200 ℃	Time above Liquidus Temperature	100sec.max
Time	60-120sec	Peak Temperature	250℃
Average ramp-up rate	3 ℃/sec.max.	Ramp- Down Rate from Peak Temperature	6 ℃/sec. max.
		Reflow times	1 time

a. Reflow soldering is recommended. Other soldering methods are not recommended as they might cause damage to the product.


b. All parameters are maximum body case temperature values and cannot be considered as a soldering profile. The body case temperature was measured by soldering a thermal couple to the soldering point of LEDs.

c. No more than one reflows welding is recommended.

Copyright © 2018 Luckylight All Rights Reserved

2. Circuit Design Notes:

a. Protective current-limiting resistors may be necessary to operate the LEDs within the specified range.
b. LEDs mounted in parallel should each be placed in series with its own current-limiting resistor.
c. The driving circuit should be designed to protect the LED against reverse voltages and transient voltage spikes when the circuit is powered up or shut down.
d. The safe operating current should be chosen after considering the maximum ambient temperature of the operating environment.



3.LED Storage Instructions

1.Store LEDs at or below 30℃ and 80% relative humidity (RH) before opening the package.
2. LEDs should be used within one year of purchase.
3. After opening the package, store LEDs at or below 30℃ and 60% RH.

Copyright © 2018 Luckylight All Rights Reserved

LuckyLight
Innovative Optoelectronic Solutions

Disclaimer

The information contained in this document is provided for technical reference only and is based on representative operating conditions.

Product part numbers, configurations, specifications and other information contained herein are subject to change or improvement without prior notice. Before product selection, design-in or mass production, customers should refer to the latest version of this datasheet and confirm the applicable specifications.

The products described in this document must be operated within the electrical, mechanical and environmental ratings specified herein. LuckyLight shall not be liable for any malfunction, damage or loss resulting from operation outside the specified ratings or from improper handling, installation or use.

The products described in this document are intended for use in standard industrial and electronic equipment, including industrial control equipment, automation systems, communication equipment, office equipment and general electronic devices.

For applications requiring exceptionally high levels of reliability or safety, where product failure could directly result in personal injury, loss of life or significant property damage, including aerospace systems, transportation systems, traffic control equipment, medical life-support equipment and safety-critical devices, please contact a LuckyLight sales representative in advance for technical evaluation and written approval.

No part of this document may be reproduced, distributed or transmitted in any form or by any means without prior written permission from LuckyLight.

Copyright © 2018 Luckylight All Rights Reserved

Revision History

Revision	Date	Contents	Page
Rev. 1	November 20, 2018	Original Version	/

Copyright © 2018 Luckylight All Rights Reserved